

# Technical specifications

## COMBI STEAM OVENS

GENERAL DESCRIPTION	OCS8687A/S/B	OCS8664A/S/B	OCS8487A/S/B	OCS8464A/S/B
Type	Combi steam	Combi steam	Combi steam	Combi steam
Installation	Built-in	Built-in	Built-in	Built-in
Size (cm)	60 cm	60 cm	45 cm	45 cm
Display	TFT Colour 6.1 inch	TFT Colour 3.0 Inch	TFT Colour 6.1 inch	TFT Colour 3.0 Inch
Colour	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel
Capacity	73 litre	73 litre	50 litre	50 litre
Energy class	A+	A+	A+	A+
<b>CONSTRUCTION &amp; PERFORMANCE</b>				
Vaulted cavity ceiling / Double infra heaters	■ / ■	■ / ■	■ / ■	■ / ■
Meat probe / Multi steam injection system	■ / ■	■ / ■	■ / ■	■ / ■
Inverter microwave system	-	-	-	-
Temperature range	30 - 230 °C	30 - 230 °C	30 - 230 °C	30 - 230 °C
Microwave power range	-	-	-	-
<b>USE &amp; FLEXIBILITY</b>				
Available baking levels	5	5	4	4
Fully extendable rails levels	2	1	1	1
Locking function on rails	■	-	■	-
Number of trays and grids	6	6	4	4
Shallow tray	2	2	1	1
Deep tray	1	1	-	-
Grill rack premium / grill rack standard	1 / -	1 / -	1 / -	1 / -
Glass tray	-	-	-	-
Small steam trays with holes	-	-	-	-
Steam tray wide with holes	1	1	1	1
Steam tray wide without holes	1	1	1	1
<b>FUNCTIONS &amp; PROGRAMMES</b>				
Auto programmes	160	160	160	160
Oven functions	25	25	25	25
Multiphase step cooking	■	■	■	■
Auto roast mode	■	■	■	■
Sous vide steam cooking	■	■	■	■
Direct steam injection	■	■	■	■
Full steam function	■	■	■	■
Microwave & hot air	-	-	-	-
<b>DESIGN &amp; INTEGRATION</b>				
Full glass front / Metal knobs	■ / ■	■ / ■	■ / ■	■ / ■
Tinted door glass / Adjustable feet	■ / ■	■ / ■	■ / ■	■ / ■
Product height / depth / width (mm)	597 / 546 / 595	597 / 546 / 595	458 / 547 / 597	458 / 547 / 597
Niche height / depth / width (mm)	590 / 550 / 560	590 / 550 / 560	450 / 550 / 560	450 / 550 / 560
<b>SAFETY &amp; MAINTENANCE</b>				
Active cavity cooling	■	■	■	■
Number of heat reflective glasses	4	4	4	4
Soft closing door / Soft opening door	■ / -	■ / -	■ / -	■ / -
Key lock / Door lock	■ / -	■ / -	■ / -	■ / -
Pyrolytic cleaning	-	-	-	-
Steam cleaning	■	■	■	■
Aqua cleaning	-	-	-	-
<b>TECHNICAL DATA</b>				
Connection rating (W)	3400 W	3400 W	3400 W	3400 W
Rated current (A)	16 A	16 A	16 A	16 A
Supply voltage (V)	220-240 V	220-240 V	220-240 V	220-240 V
Frequency (Hz)	50 Hz	50 Hz	50 Hz	50 Hz