

Technical specifications

MICROWAVE OVENS

GENERAL DESCRIPTION	OCM8487A/S/B	OCM8464A/S/B	OM8487A/S/B	OM8464A/S/B
Type	Combi micro	Combi micro	Micro	Micro
Installation	Built-in	Built-in	Built-in	Built-in
Size (cm)	45 cm	45 cm	45 cm	45 cm
Display	TFT Colour 6.1 inch	TFT Colour 3.0 Inch	TFT Colour 6.1 inch	TFT Colour 3.0 Inch
Colour	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel
Capacity	50 litre	50 litre	50 litre	50 litre
Energy class	-	-	-	-
CONSTRUCTION & PERFORMANCE				
Vaulted cavity ceiling / Double infra heaters	■ / ■	■ / ■	■ / -	■ / -
Meat probe / Multi steam injection system	- / -	- / -	- / -	- / -
Inverter microwave system	■	■	■	■
Temperature range	30 - 275 °C	30 - 275 °C	-	-
Microwave power range	90-1000 W	90-1000 W	90-1000 W	90-1000 W
USE & FLEXIBILITY				
Available baking levels	2	2	5	5
Fully extendable rails levels	-	-	-	-
Locking function on rails	-	-	-	-
Number of trays and grids	2	2	2	2
Shallow tray	1	1	1	1
Deep tray	-	-	-	-
Grill rack premium / grill rack standard	1 / -	1 / -	1 / -	1 / -
Glass tray	-	-	-	-
Small steam trays with holes	-	-	-	-
Steam tray wide with holes	-	-	-	-
Steam tray wide without holes	-	-	-	-
FUNCTIONS & PROGRAMMES				
Auto programmes	120	120	67	67
Oven functions	21	21	4	4
Multiphase step cooking	■	■	■	■
Auto roast mode	■	■	-	-
Sous vide steam cooking	-	-	-	-
Direct steam injection	-	-	-	-
Full steam function	-	-	-	-
Microwave & hot air	■	■	-	-
DESIGN & INTEGRATION				
Full glass front / Metal knobs	■ / ■	■ / ■	■ / ■	■ / ■
Tinted door glass / Adjustable feet	■ / ■	■ / ■	■ / ■	■ / ■
Product height / depth / width (mm)	458 / 547 / 597	458 / 547 / 597	458 / 547 / 597	458 / 547 / 597
Niche height / depth / width (mm)	450 / 550 / 560	450 / 550 / 560	450 / 550 / 560	450 / 550 / 560
SAFETY & MAINTENANCE				
Active cavity cooling	■	■	■	■
Number of heat reflective glasses	4	4	4	4
Soft closing door / Soft opening door	■ / -	■ / -	■ / -	■ / -
Key lock / Door lock	■ / -	■ / -	■ / -	■ / -
Pyrolytic cleaning	-	-	-	-
Steam cleaning	■	■	-	-
Aqua cleaning	-	-	■	■
TECHNICAL DATA				
Connection rating (W)	2200 W	2200 W	2200 W	2200 W
Rated current (A)	16 A	16 A	16 A	16 A
Supply voltage (V)	220-240 V	220-240 V	220-240 V	220-240 V
Frequency (Hz)	50 Hz	50 Hz	50 Hz	50 Hz