

Technical specifications

PYROLYTIC OVENS

GENERAL DESCRIPTION	OP8687A/S/B	OP8664A/S/B	OP8487A/S
Type	Pyrolytic	Pyrolytic	Pyrolytic
Installation	Built-in	Built-in	Built-in
Size	60 cm	60 cm	45 cm
Display	TFT Colour 6.1 inch	TFT Colour 3.0 Inch	TFT Colour 6.1 inch
Colour	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel	Black Steel/Graphite black /Stainless steel
Capacity	71 litre	71 litre	48 litre
Energy class	A	A	A
CONSTRUCTION & PERFORMANCE			
Vaulted cavity ceiling / Double infra heaters	■ / ■	■ / ■	■ / ■
Meat probe / Multi steam injection system	■ / ■	- / -	■ / -
Inverter microwave system	-	-	-
Temperature range	30 - 275 °C	30 - 275 °C	30 - 275 °C
Microwave power range	-	-	-
USE & FLEXIBILITY			
Available baking levels	5	5	4
Fully extendable rails levels	2	1	2
Locking function on rails	■	-	■
Number of trays and grids	4	4	3
Shallow tray	2	2	2
Deep tray	1	1	-
Grill rack premium / grill rack standard	1 / -	1 / -	1 / -
Glass tray	-	-	-
Small steam trays with holes	-	-	-
Steam tray wide with holes	-	-	-
Steam tray wide without holes	-	-	-
FUNCTIONS & PROGRAMMES			
Auto programmes	87	87	87
Oven functions	18	18	18
Multiphase step cooking	■	■	■
Auto roast mode	■	■	■
Sous vide steam cooking	-	-	-
Direct steam injection	-	-	-
Full steam function	-	-	-
Microwave & hot air	-	-	-
DESIGN & INTEGRATION			
Full glass front / Metal knobs	■ / ■	■ / ■	■ / ■
Tinted door glass / Adjustable feet	■ / ■	■ / ■	■ / ■
Product height/depth/width (mm)	597 / 546 / 595	597 / 546 / 595	458 / 547 / 597
Niche height/depth/width (mm)	590 / 550 / 560	590 / 550 / 560	450 / 550 / 560
SAFETY & MAINTENANCE			
Active cavity cooling	■	■	■
Number of heat reflective glasses	4	4	4
Soft closing door / Soft opening door	■ / -	■ / -	■ / -
Key lock / Door lock	■ / ■	■ / ■	■ / ■
Pyrolytic cleaning	■	■	■
Steam cleaning	-	-	-
Aqua cleaning	-	-	-
TECHNICAL DATA			
Connection rating	3400 W	3400 W	2600 W
Rated current	16 A	16 A	16 A
Supply voltage	220-240 V	220-240 V	220-240 V
Frequency	50 Hz	50 Hz	50 Hz